

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 857 571 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:  
12.08.1998 Bulletin 1998/33

(51) Int. Cl.<sup>6</sup>: B41J 2/01

(21) Application number: 98101195.0

(22) Date of filing: 23.01.1998

(84) Designated Contracting States:  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: Watanabe, Kazuaki  
Suwa-shi, Nagano-ken (JP)

(30) Priority: 24.01.1997 JP 11735/97  
16.01.1998 JP 6449/98  
20.01.1998 JP 8710/98

(74) Representative:  
Grünecker, Kinkeldey,  
Stockmair & Schwanhäusser  
Anwaltssozietät  
Maximilianstrasse 58  
80538 München (DE)

(71) Applicant:  
Seiko Epson Corporation  
Shinjuku-ku, Tokyo-To (JP)

(54) Ink jet recording apparatus and tank for reaction solution

(57) A tank, containing a reaction solution, for use in an ink jet recording apparatus for depositing two liquids, that is, a reaction solution, containing a polyvalent metal salt, and an ink composition, onto a recording medium to conduct printing. This tank can solve a clogging problem of the reaction solution. A reaction solution containing a polyvalent metal salt is sealed into a reaction

solution tank under reduced pressure. This prevents the reaction solution from creating a precipitate and, even after storage of the reaction solution for a long period of time, can realize good printing, especially clogging-free, stable printing.




FIG. 1

EP 0 857 571 A2

**Description****BACKGROUND OF THE INVENTION**5 **Field of the Invention**

The present invention relates to an ink jet recording apparatus wherein a reaction solution and an ink composition are deposited onto a recording medium to conduct printing and also relates to a tank containing the reaction solution for use in the ink jet recording apparatus.

10 **Background Art**

An ink jet recording method is a printing method wherein droplets of an ink composition are ejected and deposited onto a recording medium such as paper. This method has a feature that an image having a high resolution and a high quality can be printed at a high speed with a relatively inexpensive apparatus. In general, the ink composition used in the ink jet recording comprises water as a main component and, added thereto, a colorant and a wetting agent, such as glycerin, for prevention of clogging and other purposes.

15 A new ink jet recording method has been recently proposed which comprises applying a polyvalent metal salt solution onto a recording medium and then applying an ink composition containing a dye having at least one carboxyl group (for example, Japanese Patent Laid-Open No. 202328/1993).

Further, several other ink jet recording methods have also been proposed wherein two liquids, i.e., a polyvalent metal salt solution and an ink composition, are printed (for example, Japanese Patent Laid-Open Nos. 63185/1989, 240557/1991, 240558/1991, 52868/1996, and 207424/1997).

25 The claimed advantage of the ink jet recording methods using the two liquids is that, upon printing of the polyvalent metal solution (hereinafter often referred to as "reaction solution") and the ink composition onto a recording medium, the polyvalent metal salt combines mainly with a colorant to form an insoluble complex which can yield an image having water resistance and a high quality free from color bleeding.

30 The salt of a polyvalent metal, however, has low solubility in water. Therefore, use of a polyvalent metal salt solution after storage for a long period of time results in such an unfavorable phenomenon that a precipitate clogs a filter, inhibiting the reaction solution from being fed into a recording head, or otherwise the precipitate enters the recording head to unfavorably clog a fine nozzle.

**SUMMARY OF THE INVENTION**

35 The present inventor has now found that, in the ink jet recording apparatus wherein two liquids are printed to form an image, sealing of a solution containing a polyvalent metal salt into a reaction solution tank under reduced pressure can realize good printing, especially clogging-free, stable printing even after storage for a long period of time. The present invention has been made based on such finding.

Accordingly, an object of the present invention is to provide an ink jet recording apparatus, capable of realizing good printing, wherein two liquids are printed, and a reaction solution tank used therefor.

40 According to one aspect of the present invention, there is provided an ink jet recording apparatus for depositing a reaction solution, containing a polyvalent metal salt, and an ink composition onto a recording medium to conduct printing, said ink jet recording apparatus comprising: a reaction solution tank containing the reaction solution; and an ink composition tank containing the ink composition, the reaction solution tank containing the reaction solution sealed therein under reduced pressure.

45 According to another aspect of the present invention, there is provided a reaction solution tank, containing a reaction solution, for use in an ink jet recording apparatus for depositing a reaction solution, containing a polyvalent metal salt, and an ink composition onto a recording medium to conduct printing, the reaction solution tank containing the reaction solution sealed therein under reduced pressure.

50 **BRIEF DESCRIPTION OF THE DRAWING**

Fig. 1 is a perspective view of an ink jet recording apparatus according to the present invention;

55 Fig. 2 is an explanatory cross-sectional view of an embodiment of the ink jet recording apparatus according to the present invention; and

Fig. 3 is an exploded, perspective view of a reaction solution tank for the ink jet recording apparatus according to the present invention.

DETAILED DESCRIPTION OF THE INVENTIONInk jet recording apparatus and reaction solution tank

5 The ink jet recording apparatus and the reaction solution tank according to the present invention will be described with reference to the accompanying drawings.

Fig. 1 is a diagram showing one embodiment of the ink jet recording apparatus according to the present invention. The apparatus shown in the drawing comprises a carriage 2 which is reciprocated in a direction indicated by an arrow B on a guide shaft 2a along a platen 1 as recording paper carrying means rotated in a direction indicated by an arrow A for carrying recording paper. The carriage 2 is loaded with a recording head 3a for ejecting a reaction solution in a position close to the platen 1 and a recording head 3b for ejecting an ink composition. A tank 7a for a reaction solution is provided above the recording head 3a, while a tank 7b for an ink composition is provided above the recording head 3b. A reaction solution from the reaction solution tank 7a and an ink composition from the ink composition tank 7b are fed respectively into the recording head 3a and the recording head 3b.

15 A signal is sent to the recording heads 3a and 3b through a signal cable 18, and, in response to the signal, droplets of the reaction solution or droplets of the ink composition are ejected from the recording head 3a or 3b through a nozzle (not shown). The ejected droplets of the reaction solution or the ink composition are deposited onto a recording medium 20 (for example, paper) wound around the platen 1 to yield an image.

When clogging has occurred in the recording head, the nozzle face of the recording head is sealed with a cap member 13, followed by suction of the reaction solution or the ink composition by means of a pump 15 connected through the cap member 13 and a conduit 14 to eliminate the clogging. The sucked reaction solution or ink composition is led to a waste tank 17 through a conduit 16.

In the drawing, only one cap member is provided. Alternatively, a plurality of cap members may be provided respectively for the recording heads 3a and 3b.

25 The reaction solution tank according to the present invention will be described. Fig. 2 is a cross-sectional view of the ink jet recording apparatus shown in Fig. 1, and Fig. 3 is an exploded, perspective view of a reaction solution tank 7a. A reaction solution tank 7a having a reaction solution reservoir 6 housing therein a foam 6a constituted by a porous member, such as a polyurethane foam, is provided above the recording head 3a. The reaction solution tank 7a has a lid 8 provided with a communicating hole 9 communicated with the outside of the reaction solution tank. On the other hand, a base-like protrusion 10 is provided on the bottom face so as to intimately contact with the foam 6a. There is a communicating section, communicated with the recording head 3a, extending downward from the center portion of the protrusion 10. The communicating section comprises a reaction solution chamber 11 for withdrawing and holding the reaction solution contained in the foam 6a and a cap 12, constituted by an elastic member, such as rubber, provided at the end of the reaction solution chamber 11.

35 Insertion of a hollow needle 5 as a communicating member communicated with the recording head 3a and a filter chamber 4 provided on the carriage into the cap 12 permits the reaction solution impregnated within the reaction solution tank 7a to be fed into the recording head 3a.

At least one communicating hole 9 is placed in a sealed state using an openable, gas-impermeable sealing member 21 under reduced pressure until immediately before use. Immediately before use, the gas-impermeable sealing member 21 is opened to communicate the reaction solution tank 7a with the outside of the reaction solution tank 7a through an air hole 9a. Preferably, the sealing member 21 is constructed so that, as shown in Fig. 3, it has a satisfactory long section and can be easily opened by picking up the end of the long section. During printing, the air hole 9a functions to replenish the reaction solution tank 7a with air by a volume equal to the volume of the consumed reaction solution.

45 In the reaction solution tank according to the present invention, the reaction solution is contained in the reaction solution tank under reduced pressure. The air hole 9a has been sealed. The reaction solution under reduced pressure does not create a precipitate. Consequently, the reaction solution, when used in printing after mounting on an ink jet recording apparatus, neither causes clogging of the filter with the precipitate nor causes the precipitate to flow into the recording head to unfavorably clog a fine nozzle. Thus, use of a reaction solution filled into the reaction solution tank according to the present invention enables clogging-free, stable printing.

According to a preferred embodiment of the present invention, the pressure in the reaction solution tank is less than atmospheric pressure, preferably not more than 0.05 MPa, and more preferably not more than 0.02 MPa.

55 The reaction solution tank according to the present invention is preferably produced by the following process. First, the reaction solution tank 7 is assembled, while the sealing members 21 and 22 are not assembled. The reaction solution reservoir 6 in the reaction solution tank 7 is evacuated through the communicating hole 9. The degree of evacuation may be properly determined. When the amount of the reaction solution filled and the filling time are taken into consideration, however, the reaction solution tank is evacuated to a pressure of preferably not more than 0.05 MPa, more preferably not more than 0.02 MPa. Subsequently, the reaction solution is filled into the reaction solution tank through the

communicating hole 9. At that time, the pressure of the reaction solution is reduced to provide a deaerated reaction solution. The communicating hole 9 except for the air hole 9a is sealed with the sealing member 22 under atmospheric pressure. Thereafter, in the step of vacuum hermetic sealing, the reaction solution tank 7 is evacuated, and the air hole 9a is sealed with the sealing member 21. According to a preferred embodiment of the present invention, the internal pressure of the reaction solution reservoir 6 is reduced to not more than 0.05 MPa, more preferably not more than 0.02 MPa.

#### Reaction solution

According to the present invention, the reaction solution comprises at least a polyvalent metal salt.

The polyvalent metal salt usable in the reaction solution is constituted by divalent or higher polyvalent metallic ions and anions bonded to the polyvalent metallic ions and is soluble in water. Specific examples of polyvalent metallic ions include divalent metallic ions, such as  $\text{Ca}^{2+}$ ,  $\text{Cu}^{2+}$ ,  $\text{Ni}^{2+}$ ,  $\text{Mg}^{2+}$ ,  $\text{Zn}^{2+}$ , and  $\text{Ba}^{2+}$ , trivalent metallic ions, such as  $\text{Al}^{3+}$ ,  $\text{Fe}^{3+}$ , and  $\text{Cr}^{3+}$ . Anions include  $\text{Cl}^-$ ,  $\text{NO}_3^-$ ,  $\text{I}^-$ ,  $\text{Br}^-$ ,  $\text{ClO}_3^-$ , and  $\text{CH}_3\text{COO}^-$ .

Especially, a metal salt constituted by  $\text{Ca}^{2+}$  or  $\text{Mg}^{2+}$  provides favorable results in terms of pH of the reaction solution and the quality of prints.

The concentration of the polyvalent metal salt in the reaction solution may be suitably determined so as to attain the effect of providing a good print quality and preventing clogging. It, however, is preferably about 0.1 to 40% by weight, more preferably about 5 to 25% by weight.

According to a preferred embodiment of the present invention, the reaction solution contains a wetting agent comprising a high-boiling organic solvent. The high-boiling organic solvent serves to prevent the reaction solution from being concentrated due to evaporation, thus preventing clogging of a recording head. Preferred examples of high-boiling organic solvents usable herein include: polyhydric alcohols such as ethylene glycol, diethylene glycol, triethylene glycol, polyethylene glycol, propylene glycol, polypropylene glycol, butylene glycol, hexylene glycol, 1,2,6-hexanetriol, thioglycol, glycerin, trimethylethane, and trimethylolpropane; alkyl ethers of polyhydric alcohols, such as ethylene glycol monomethyl ether, ethylene glycol monoethyl ether, ethylene glycol monobutyl ether, diethylene glycol monomethyl ether, diethylene glycol monoethyl ether, diethylene glycol monobutyl ether, triethylene glycol monomethyl ether, and triethylene glycol monoethyl ether, and triethylene glycol monobutyl ether; 2-pyrrolidone; N-methyl-2-pyrrolidone; 1,3-dimethyl-2-imidazolidinone; and triethanolamine.

Although the amount of the high-boiling organic solvent added is not particularly limited, it is preferably about 0.5 to 40% by weight, more preferably about 2 to 20% by weight.

According to a preferred embodiment of the present invention, the reaction solution comprises a low-boiling organic solvent. Preferred examples of low-boiling organic solvents usable herein include methanol, ethanol, n-propyl alcohol, iso-propyl alcohol, n-butanol, sec-butanol, tert-butanol, iso-butanol, and n-pentanol. Monohydric alcohols are particularly preferred. The low-boiling organic solvent has the effect of shortening the time taken for drying the ink. The amount of the low-boiling organic solvent added is preferably in the range of from 0.5 to 10% by weight, more preferably in the range of from 1.5 to 6% by weight.

According to a preferred embodiment of the present invention, the reaction solution comprises a penetrating agent. Penetrating agents usable herein include various surfactants such as anionic, cationic, and amphoteric surfactants; alcohols such as methanol, ethanol, and isopropyl alcohol; and lower alkyl ethers of polyhydric alcohols, such as ethylene glycol monomethyl ether, diethylene glycol monoethyl ether, diethylene glycol monobutyl ether, triethylene glycol monobutyl ether, propylene glycol monobutyl ether, and dipropylene glycol monobutyl ether.

#### Ink composition

The ink composition used in the present invention comprises at least a colorant, an organic solvent, water, and preferably a resin emulsion. The colorant may be any of a dye and a pigment. Dyes usable herein include various dyes commonly used in ink jet recording, such as direct dyes, acid dyes, foodstuff dyes, basic dyes, reactive dyes, disperse dyes, and vat dyes. Regarding the pigment, inorganic and organic pigments are usable without any particular limitation. The pigment is generally added, to the ink, as a pigment dispersion prepared by dispersing the pigment in an aqueous medium with the aid of a dispersant. Many of the dyes and pigments react with polyvalent metallic ions contained in the reaction solution to produce a metal complex insoluble or sparingly soluble in water, yielding a print having sharp edge and free from color bleeding.

A resin emulsion also reacts with polyvalent metallic ions to produce an insoluble complex. Therefore, the addition of the resin emulsion can greatly contribute to an improvement in print quality.

The ink composition may further comprise an organic solvent. Further, addition of other components is not particularly limited. Especially, incorporation of a component, which can react with polyvalent metallic ions to produce a complex insoluble or sparingly soluble in water, into the ink composition is preferred. In general, the ink composition

comprises water as a main component and, added thereto, a colorant and a wetting agent, such as glycerin, for prevention of clogging and other purposes.

### EXAMPLES

The present invention will be described in more detail with reference to the following examples, though it is not limited to these examples only.

Reaction solution 1	
Magnesium nitrate hexahydrate	25 wt%
Triethylene glycol monobutyl ether	10 wt%
Glycerin	20 wt%
Triethanolamine	0.9 wt%
Pure water	Balance

Reaction solution 2	
Magnesium nitrate hexahydrate	5 wt%
Triethylene glycol monobutyl ether	10 wt%
Glycerin	20 wt%
Triethanolamine	0.9 wt%
Pure water	Balance

Reaction solution 3	
Calcium nitrate tetrahydrate	10 wt%
Triethylene glycol monobutyl ether	10 wt%
Glycerin	20 wt%
Triethanolamine	0.9 wt%
Pure water	Balance

### Filling of reaction solution into tank

Each of the above reaction solutions was filled into a reaction solution tank. In particular, a tank having a basic structure shown in Fig. 2 was assembled, and the reaction solution reservoir 6 of the assembled reaction solution tank 7 was evacuated to a pressure of not more than 0.05 MPa through the communicating hole 9. Subsequently, the reaction solution was then filled into the reaction solution tank through the communicating hole 9. The communicating hole 9 except for the air hole 9a was then sealed with a sealing member 22. Thereafter, in the step of hermetic sealing, the reaction solution tank 7 was evacuated, and the communicating hole 9a was sealed with a sealing member 21. The reaction solution tank was evacuated to two levels of pressure as specified in Table 1, that is, 0.05 MPa and 0.02 MPa. Further, for comparison, the evacuation was not performed after filling of the reaction solution, and the sealing was con-

ducted under atmospheric pressure. These three tanks respectively having three levels of pressure in sealed state were provided for each of the reaction solutions 1 to 3. The reaction solution tanks were then subjected to an accelerated test corresponding to a storage under ordinary temperature and ordinary humidity conditions for one year.

#### 5 Printing test

The solution tank which was subjected to the accelerated test above was loaded onto an ink jet printer MJ-510C (manufactured by Seiko Epson Corporation). A pattern containing a combination of characters with graphics was continuously printed on paper of size A4. At that time, ejection of droplets of the reaction solution from the nozzle was visually inspected, and the results were evaluated according to the following criteria.

A: Number of sheets printable without "dropout" and "ejection of droplets with trajectories non-perpendicular to the print head", 500 or more

15 B: Number of sheets printable without "dropout" and "ejection of droplets with trajectories non-perpendicular to the print head", 300 to less than 500

C: Number of sheets printable without "dropout" and "ejection of droplets with trajectories non-perpendicular to the print head", 100 to less than 300

20 NG: Number of sheets printable without "dropout" and "ejection of droplets with trajectories non-perpendicular to the print head", less than 100.

The results of evaluation were as summarized in the following table.

Table 1

	Example 1	Example 2	Comparative Example
Pressure of reaction solution tank (MPa)	0.05	0.02	Atmospheric pressure
Reaction solution 1	B	A	C
Reaction solution 2	A	A	C
Reaction solution 3	A	A	NG

#### 35 Claims

1. An ink jet recording apparatus for depositing a reaction solution, containing a polyvalent metal salt, and an ink composition onto a recording medium,

40 said ink jet recording apparatus comprising: a reaction solution tank containing the reaction solution; and an ink composition tank containing the ink composition,  
the reaction solution tank containing the reaction solution sealed therein under reduced pressure.

2. The ink jet recording apparatus according to claim 1, wherein the reduced pressure is a pressure of less than atmospheric pressure.

- 45 3. The ink jet recording apparatus according to claim 1, wherein the reduced pressure is a pressure of not more than 0.05 MPa.

- 50 4. A reaction solution tank, containing a reaction solution, for use in an ink jet recording apparatus for depositing a reaction solution, containing a polyvalent metal salt, and an ink composition onto a recording medium to conduct printing,

the reaction solution tank containing the reaction solution sealed therein under reduced pressure.

- 55 5. The reaction solution according to claim 4, wherein the reduced pressure is a pressure of less than atmospheric pressure.

6. The reaction solution tank according to claim 4, wherein the reduced pressure is a pressure of not more than 0.05

MPa.

- 5 7. A reaction solution tank, containing a reaction solution, for use in an ink jet recording apparatus for depositing a reaction solution, containing a polyvalent metal salt, and an ink composition onto a recording medium to conduct printing,

10 the reaction solution tank comprising: a reaction solution reservoir; a communicating section communicated with the reaction solution reservoir and a recording head; at least one communicating hole communicated with the outside of the reaction tank; and a gas-impermeable sealing member for hermetically sealing the communicating hole, the reaction solution being sealed into the reaction solution reservoir under reduced pressure.

8. The reaction solution tank according to claim 7, wherein the reduced pressure is a pressure of less than atmospheric pressure.

- 15 9. The reaction solution tank according to claim 7, wherein the reduced pressure is a pressure of not more than 0.05 MPa.

- 20 10. A process for producing a reaction solution tank, containing a reaction solution, for use in an ink jet recording apparatus for depositing a reaction solution, containing a polyvalent metal salt, and an ink composition onto a recording medium to conduct printing, said reaction solution tank comprising: a reaction solution reservoir; a communicating section communicated with the reaction solution reservoir and a recording head; at least one communicating hole communicated with the outside of the reaction tank; and a gas-impermeable sealing member for hermetically sealing the communicating hole,

25 said process comprising the steps of:

- 25 (a) evacuating the reaction solution reservoir through the communicating hole;  
(b) feeding and filling the reaction solution through the communicating hole into the reaction solution tank; and  
(c) evacuating the reaction solution reservoir and hermetically sealing the reaction solution reservoir in an evacuated state with the gas-impermeable sealing member.

- 30 11. The process according to claim 10, wherein, in the step (c), the reaction solution reservoir is evacuated to a pressure of less than atmospheric pressure.

- 35 12. The process according to claim 10, wherein, in the step (c), the reaction solution reservoir is evacuated to a pressure of not more than 0.05 MPa.




FIG. 1






FIG. 2





FIG. 3



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 857 571 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
**06.05.1999 Bulletin 1999/18**

(51) Int. Cl.<sup>6</sup>: **B41J 2/01**

(43) Date of publication A2:  
**12.08.1998 Bulletin 1998/33**

(21) Application number: **98101195.0**

(22) Date of filing: **23.01.1998**

(84) Designated Contracting States:  
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Watanabe, Kazuaki**  
**Suwa-shi, Nagano-ken (JP)**


(74) Representative:  
**Grünecker, Kinkeldey,  
Stockmair & Schwanhäusser  
Anwaltssozietät  
Maximilianstrasse 58  
80538 München (DE)**

(30) Priority: **24.01.1997 JP 11735/97**  
**16.01.1998 JP 6449/98**  
**20.01.1998 JP 8710/98**

(71) Applicant:  
**Seiko Epson Corporation**  
**Shinjuku-ku, Tokyo-To (JP)**

(54) **Ink jet recording apparatus and tank for reaction solution**

(57) A tank (7a), containing a reaction solution, for use in an ink jet recording apparatus for depositing two liquids, that is, a reaction solution, containing a polyvalent metal salt, and an ink composition, onto a recording medium to conduct printing. This tank (7a) can solve a clogging problem of the reaction solution. A reaction solution containing a polyvalent metal salt is sealed into a reaction solution tank (7a) under reduced pressure. This prevents the reaction solution from creating a precipitate and, even after storage of the reaction solution for a long period of time, can realize good printing, especially clogging-free, stable printing.



**FIG. 1**

**EP 0 857 571 A3**



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 98 10 1195

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP 0 534 634 A (HEWLETT PACKARD CO) 31 March 1993 * claim 1 *	1,4,7,10	B41J2/01
D	& JP 05 202328 A (HEWLETT PACKARD CO) 10 August 1993 ---		
A	US 4 914 453 A (KANAYAMA YOSHIO ET AL) 3 April 1990 * column 3, paragraph 2; claim 1; figure 6 *	1,4,7,10	
A	EP 0 738 605 A (CANON KK) 23 October 1996 * abstract * * page 2, line 1 - line 22; figure 1 * -----	1,4,7,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B41J
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 12 March 1999	Examiner Wehr, W
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 10 1195

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

12-03-1999

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0534634	A	31-03-1993	JP	5202328 A	10-08-1993
US 4914453	A	03-04-1990	DE	3913456 A	02-11-1989
EP 0738605	A	23-10-1996	JP	9267483 A	14-10-1997
			AU	4678097 A	12-02-1998
			AU	4678497 A	12-02-1998
			AU	4678597 A	19-02-1998
			AU	5070696 A	02-01-1997
			AU	7881498 A	08-10-1998
			CA	2174285 A	18-10-1996
			CN	1137978 A	18-12-1997

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office. No. 12/82